



Electromagnetic flow meters

The company



About us

Badger Meter Europa GmbH is a wholly owned subsidiary of Badger Meter, Inc., USA, based in Milwaukee, Wisconsin. With sales of more than 350 million Euro and the dedication of more than 1450 employees all around the world, Badger Meter is a leading marketer and manufacturer of flow measurement and control devices since 1905. Badger Meter was a pioneer in flow measurement and can look back today at many patents in that field.

Badger Meter Europa GmbH is responsible for the international operations worldwide, except for the United States, Mexico, Canada and Latin America which are operated from Badger Meter, Inc., USA. Highly qualified people as well as state-of-the-art production and test facilities ensure the best sales support and service for our customers.

Customer proximity & competence

We can help you in a timely manner to solve your measurement problems, advising you to assist in optimizing your measurement solution, technology and site location before you make a decision.

An extensive distributor and service network ensures the best service worldwide. Local representatives are a big advantage for our customers. The short distance and local language support provide efficient service. Our distributors are trained on Badger Meter products at their own facilities or in our training center.

Our name assures you that our products have been manufactured with the best care and in conformity with all DIN ISO 9001:2008 directives.

Quality is our tradition

A company which has successfully been providing the industry with flow meters for more than 110 years is always aware of the importance of quality in its products. However, quality is an on-going process which we, as a company, embrace every day. At Badger Meter Europa GmbH, we consider quality in all aspects of our operation. It is the quality of our work, which you, as a customer, are entitled to expect from us. Quality begins with the individual, our employees, and requires a company philosophy which fits accordingly. Our quality should accompany you throughout the process: from inquiry, through order to product and service. No compromise in terms of quality.

Service

Urgent orders may be delivered overnight with our „Hot-Shot“ service.



Electromagnetic flow meters


Electromagnetic flow meters are ideally suited for flow measurement of all liquids with a minimum conductivity of $5 \mu\text{S/cm}$ ($20 \mu\text{S/cm}$ for demineralized water).

These meters are very accurate and the flow measurement is independent of density, temperature and pressure of the medium.

Measuring principle

The operating principle of the electromagnetic flow meter is based on Faraday's law of magnetic induction: The voltage induced across any conductor, as it moves at right angles through a magnetic field, is proportional to the velocity of that conductor. The voltage induced within the fluid is measured by two diametrically opposed internally mounted electrodes.

The induced signal voltage is proportional to the product of the magnetic flux density, the distance between the electrodes and the average flow velocity of the fluid.



Meters for conductive fluids – Detectors



- Flange process connection
- Size DN 6 – 2000
- Nominal pressure up to PN 100


Detector type II for a great variety of applications

The electromagnetic detector type II is not only available in a number of different flange process connections (DIN, ANSI, JIS, AWWA, etc.) but also in a number of liners like hard rubber, soft rubber, PTFE, PFA or Halar.

The detector can be configured with up to four electrodes for measuring, empty pipe and grounding electrodes.

Available in sizes from DN 6 to DN 2000 and nominal pressures up to PN 100, the detector type II is best suited for a variety of applications in industry and water/waste water industry.

Lined measuring pipes with materials that are approved for drinking water: KTW/DVGW, NSF-61, WRAS, ACS.



Detector type III with short lay length

Thanks to its very short lay length, the detector type III is often the right alternative for many applications. Delivered with a PTFE liner, the detector type III has a standard nominal pressure of PN 40.

- Wafer connection
- Size DN 25 – 100
- Nominal pressure PN 40



Sanitary detector for liquid food flow measurement

The sanitary detector was developed for the flow measurement of liquid food. This model is available with Tri-Clamp® BS 4825/ISO 2852, DIN 11851 process connections and also with any special connections (customer specifications). The sanitary detector is delivered in a stainless steel housing and with PTFE lining.



- Process connections Tri-Clamp® BS 4825/ISO 2852, DIN 11851
- Size DN 10 – 100
- Nominal pressure PN 10/16

Technical data: Detectors



Type	Type II	Type III	Type Food
Size	DN 6 - 2000 (1/4" ... 80")	DN 25 - 100 (1" ... 4")	DN 10 - 100 (3/8" ... 4")
Process connections	Flange: DIN, ANSI, JIS, AWWA u.a.	Wafer connection, (in-between flange mounting)	Tri-Clamp® BS 4825/ISO 2852, DIN 11851 among others
Nominal pressure	Up to PN 100	PN 40	PN 10/16
Protection class	IP 67, optional IP 68	IP 65, optional IP 68	IP 65, optional IP 68
Min. conductivity	5 μ S/cm (min. 20 μ S/cm for demineralized water)	5 μ S/cm (min. 20 μ S/cm for demineralized water)	5 μ S/cm (min. 20 μ S/cm for demineralized water)
Liner materials	Hard/soft rubber from DN 25 0 up to +80 °C PTFE DN 6 - 600 -40 up to +150 °C Halar (ECTFE) from DN 300 -40 up to +150 °C	PTFE -40 up to +150 °C	PTFE -40 up to +150 °C
Electrodes materials	Hastelloy C (standard) Tantal Platinum / Gold plated Platinum / Rhodium	Hastelloy C (standard) Tantal Platinum / Gold plated Platinum / Rhodium	Hastelloy C (standard) Tantal Platinum / Gold plated Platinum / Rhodium
Housing	Carbon steel / optional stainless steel	Carbon steel / optional stainless steel	Stainless steel
Lay length	DN 6 - 20 170 mm DN 25 - 50 225 mm DN 65 - 100 280 mm DN 125 - 200 400 mm DN 250 - 350 500 mm DN 400 - 700 600 mm DN 750 - 1000 800 mm DN 1200 - 1400 1000 mm DN 1600 1600 mm DN 1800 1800 mm DN 2000 2000 mm or according to ISO 13359	DN 25 - 50 100 mm DN 65 - 100 150 mm	Tri-Clamp® connection: DN 10 - 50 145 mm DN 65 - 100 200 mm DIN 11851 connection: DN 10 - 20 170 mm DN 25 - 50 225 mm DN 65 - 100 280 mm

Amplifiers

Amplifier for a great variety of applications – ModMAG® M2000



The amplifier type ModMAG® M2000 is best suited for bidirectional flow measurement of fluids with a conductivity $> 5 \mu\text{S/cm}$ ($> 20 \mu\text{S/cm}$ for demineralized water). ModMAG® M2000 shows a high accuracy, is easy to use and can be chosen for a large and flexible applications spectrum.

The backlight, four-line display shows all actual flow measuring data, daily and complete information, including alarm messages.

The standard amplifier has 4 programmable digital outputs, one digital input, analog output and different interfaces.

Integrated system self check-up makes putting into operation and servicing easier.

The back-up function enables retrieval of parameters while servicing the meter, without the need for reprogramming the device or transferring to another device.

- For all detectors
- Accuracy $\pm 0,2\%$ of actual flow
- Flow range 0,03 – 12 m/s
- Size DN 6 – DN 2000
- Protection class IP 67
- Interfaces ModBus®, HART®, M-Bus, Profibus DP

Verification Device

The verification device enables the ModMAG® electromagnetic flow meters M2000 and B-MAG | M5000 to be checked on site in regular time intervals at a low cost and without interruption of the process. All important parameters of the flow meter are measured, recorded and evaluated.



Battery-powered amplifier for water supply – B-MAG | M5000

The B-MAG | M5000 is a battery-powered electromagnetic flow meter with a very high accuracy even at very low flows. The excellent repeatability as well as the above-average battery life makes this innovative water meter indispensable for the water market. Typical applications are leak detection in water networks, water consumption measurements and irrigation plants.

The meter is best suited for applications without a power supply where exact consumption or flow rates are required. The B-MAG | M5000 can also be used with an available power supply. The meter can be powered with mains voltage and in case of a mains failure, it is powered by an internal battery. Important data is therefore saved.

The B-MAG | M5000 has been designed for very harsh environmental measurement conditions. The meter has no moving parts and can be used to measure water containing particles like sand or gravel. The B-MAG | M5000 is encased in an IP 67 housing (optional IP 68), which makes it a reliable meter even when submerged.

The standard meter is equipped with an internal datalogger which can be read via an IrDA or M-Bus with ModBus® RTU protocol.

The collected data can also be retrieved via radio frequency or GSM/GPRS. The data can thus be centrally compiled and evaluated.

- For flanged process connections
- Accuracy better than $\pm 0,4\%$ of actual flow
- Flow range 0,03 to 10 m/s
- Size DN 15 – DN 600
- Protection class IP 67 / IP 68
- Interfaces IrDA, ModBus® RTU, M-Bus
- Up to 20 years battery life span



BATTERY OPERATED

Low-cost amplifier for a great variety of applications – ModMAG® M1000



- For all detectors
- Accuracy $\pm 0,3\%$ of actual flow
- Flow range 0,03 – 12 m/s
- Size DN 6 – DN 200

The ModMAG® M1000 amplifier is suited for bidirectional flow measurement of liquids $> 5 \mu\text{S/cm}$ ($> 20 \mu\text{S/cm}$ for demineralized water).

It combines all the opportunities of price with high level performance. Information such as flow rate, total flow rates, daily flow rate or even an alert can easily be read from the LCD display.

Various inputs, outputs and interfaces allow a wide range of different applications with the ModMAG® M1000. Thanks to the IP67 aluminium housing the ModMAG® M1000 is ideal for outdoor applications in rugged environmental conditions.

Amplifier for hazardous areas – ModMAG® M3000/M4000

The amplifier with modular design allows flow measurements in ex-zones 1 and 2, in either the mounted or remote version. The amplifier housing, made of powder-coated aluminium, is available in protection class IP67 and with a separate connection space.

Programming can be done either with closed housing thanks to a magnetic pen or with open housing via three buttons. The four-line display shows all necessary data like actual flow, totalizer and status messages.

The programmable excitation frequency even enables the amplifier to be adjusted for difficult metering

applications. The newly developed process for amplifier compensation enables a high accuracy, especially in the lower flow range.

The ModMAG® M3000/M4000 is especially suited for flow measurements in chemical and pharmaceutical industries, as well as water and waste water plants with explosion-proof zones.

- For all detectors
- Accuracy $\pm 0,2\%$ of actual flow
- Flow range 0,03 – 12 m/s
- Protection class IP 67
- Ex-proof




Technical data: Amplifiers



Type	ModMAG® M1000	ModMAG® M2000	ModMAG® M3000/M4000	B-MAG I M5000
Size	DN 6 – DN 200	DN 6 – DN 2000	DN 6 – DN 600 (M3000) DN 6 – DN 300 (M4000)	DN 15 – DN 600
Accuracy	± 0,3% of actual flow, ± 2 mm/s of actual flow	± 0,2% of actual flow, ± 1 mm/s of actual flow	± 0,2% of actual flow, ± 1 mm/s of actual flow	± 0,4% of actual flow, ± 2 mm/s of actual flow
Repeatability	0,1%	0,1%	0,1%	0,1%
Flow range	0,03 – 12 m/s	0,03 – 12 m/s	0,03 – 12 m/s	0,03 – 10 m/s
Conductivity	Min. 5 μ S/cm (min. 20 μ S/cm for demineralized water)	Min. 5 μ S/cm (min. 20 μ S/cm for demineralized water)	Min. 5 μ S/cm (min. 20 μ S/cm for demineralized water)	Min. 20 μ S/cm
Power supply	92 – 275 VAC (50/60 Hz) < 14 VA, optional 9 – 36 VDC, 4 W	85 – 265 VAC (50/60 Hz) < 20 VA, optional 9 – 36 VDC	85 – 265 VAC (50/60 Hz) < 20 VA, optional 24 VDC	Internal Lithium batteries 3,6 V Optional battery back-up model (100 – 240 VAC or 9 – 36 VDC)
Display	LCD graphic display	LCD 4 lines / 20 characters	LCD 4 lines / 16 characters	LCD, 2 lines
Digital outputs	2 x open collector 1 x relay	4 x open collector 2 x relays	2 x open collector 2 x relays (M3000)	4 x open collector
Digital inputs	Yes	Yes	Yes	Yes
Analog output	0/4 – 20 mA, 0 – 10 mA	0/4 – 20 mA, 0/2 – 10 mA	0/4 – 20 mA, 0 – 10 mA	–
Interface	ModBus® RTU RS232/RS485 ModBus® TCP/IP M-Bus, HART®	ModBus® RTU RS232/RS485 Profibus DP, M-Bus, HART®	–	ModBus® RTU RS232 (optional RS485), M-Bus, IrDA
Empty pipe detection	Separate electrode	Separate electrode	Separate electrode	Separate electrode
Datalogger	30.000 measuring values	10.000 measuring values (optional)	–	7.224 measuring values
Housing	Aluminium, IP 67	Aluminium, IP 67	Aluminium, IP 67 (NEMA 4x)	Aluminium, IP 67 (optional IP 68)
Remote version	Max. 50 m	Max. 100 m	Max. 30 m	Max. 30 m
Ambient temperature	-20 °C up to +60 °C	-20 °C up to +60 °C	-20 °C up to +50 °C	-20 °C up to +60 °C
Approvals	–	OIML R49-1, MID MI-001 in process	M3000 ATEX Zone 2, FM/CSA Class I, Div. 2 M4000 ATEX Zone 1, FM/CSA Class I, Div. 1	OIML R49-1, MID MI-001


Flange process connection

Wall mounted



Flange process connection

Meter mounted



Dimensions (mm)

DN (mm)	Size (inches)	A Std*	A ISO**	B 1	B 2	with ANSI-flanges			with DIN flanges		
						Ø D	Ø K	Ø d2 x n	Ø D	Ø K	Ø d2 x n
6	1/4"	170	-	228	305	88,9	60,3	15,9 x 4	90	60	14 x 4
8	3/10"	170	-	228	305	88,9	60,3	15,9 x 4	90	60	14 x 4
10	3/8"	170	-	228	305	88,9	60,3	15,9 x 4	90	60	14 x 4
15	1/2"	170	200	238	315	88,9	60,3	15,9 x 4	95	65	14 x 4
20	3/4"	170	200	238	315	98,4	69,8	15,9 x 4	105	75	14 x 4
25	1"	225	200	238	315	107,9	79,4	15,9 x 4	115	85	14 x 4
32	1 1/4"	225	200	253	330	117,5	88,9	15,9 x 4	140	100	18 x 4
40	1 1/2"	225	200	253	330	127	98,4	15,9 x 4	150	110	18 x 4
50	2"	225	200	253	330	152,4	120,6	19 x 4	165	125	18 x 4
65	2 1/2"	280	200	271	348	177,8	139,7	19 x 4	185	145	18 x 4
80	3"	280	200	271	348	190,5	152,4	19 x 4	200	160	18 x 8
100	4"	280	250	278	355	228,6	190,5	19 x 8	220	180	18 x 8
125	5"	400	250	298	375	254	215,9	22,2 x 8	250	210	18 x 8
150	6"	400	300	310	387	279,4	241,3	22,2 x 8	285	240	22 x 8
200	8"	400	350	338	415	342,9	298,4	22,2 x 8	340	295	22 x 12
250	10"	500	450	362	439	406,4	361,9	25,4 x 12	395	350	22 x 12
300	12"	500	500	425	502	482,6	431,8	25,4 x 12	445	400	22 x 12
350	14"	500	550	450	527	533,4	476,2	28,6 x 12	505	460	22 x 16
400	16"	600	600	475	552	596,9	539,7	28,6 x 16	565	515	26 x 16
450	18"	600	-	500	577	635,0	577,8	31,7 x 16	615	565	26 x 20
500	20"	600	-	525	602	698,5	635,0	31,7 x 20	670	620	26 x 20
550	22"	600	-	550	627	749,3	692,1	34,9 x 20	-	-	-
600	24"	600	-	588	665	812,8	749,3	34,9 x 20	780	725	30 x 20
650	26"	600	-	613	690	869,9	806,4	34,9 x 24	-	-	-
700	28"	600	-	625	702	927,1	863,6	35,1 x 28	895	840	30 x 24
750	30"	800	-	650	727	984,2	914,4	34,9 x 28	-	-	-
800	32"	800	-	683	760	1060,5	977,9	41,3 x 28	1015	950	33 x 24
850	34"	800	-	708	785	1111,2	1028,7	41,3 x 32	-	-	-
900	36"	800	-	725	802	1168,4	1085,8	41,3 x 32	1115	1050	33 x 28
950	38"	800	-	750	827	1238,3	1149,4	41,3 x 32	-	-	-
1000	40"	800	-	790	867	1346,2	1257,3	41,3 x 36	1230	1160	36 x 28
1200	48"	1000	-	900	977	1511,5	1422,4	41,3 x 44	1455	1380	39 x 32
1350	54"	1000	-	975	1052	1682,8	1593,9	47,8 x 44	-	-	-
1400	56"	1000	-	1000	1077	-	-	-	1675	1590	42 x 36

Standard

with ANSI flanges	from DN 6 to 1400	Lbs 150
with DIN flanges	from DN 6 to 200	PN 16
	from DN 250 to 1400	PN 10

*Standard **ISO 13359
 Sizes DN 1600 – 2000 upon request.

Flow range					
DN (mm)	Size (inches)	0,03 m/s	2,5 m/s	10 m/s	12 m/s
6	1/4"	0,05 l/min	4,2 l/min	17 l/min	20 l/min
8	3/10"	0,09 l/min	7,5 l/min	30,2 l/min	36 l/min
10	3/8"	0,14 l/min	12 l/min	47,1 l/min	57 l/min
15	1/2"	0,32 l/min	27 l/min	106 l/min	127 l/min
20	3/4"	0,57 l/min	47 l/min	188,5 l/min	226 l/min
25	1"	0,88 l/min	74 l/min	294,5 l/min	353 l/min
32	1 1/4"	1,45 l/min	121 l/min	483 l/min	579 l/min
40	1 1/2"	2,3 l/min	188 l/min	754 l/min	905 l/min
50	2"	3,5 l/min	295 l/min	1178 l/min	1414 l/min
65	2 1/2"	6,0 l/min	498 l/min	1991 l/min	2389 l/min
80	3"	9,0 l/min	754 l/min	3016 l/min	3619 l/min
100	4"	14 l/min	1178 l/min	4712 l/min	5655 l/min
125	5"	1,33 m³/h	110 m³/h	442 m³/h	530 m³/h
150	6"	1,9 m³/h	159 m³/h	636 m³/h	763 m³/h
200	8"	3,4 m³/h	283 m³/h	1131 m³/h	1357 m³/h

Flow range					
DN (mm)	Size (inches)	0,03 m/s	2,5 m/s	10 m/s	12 m/s
250	10"	5,3 m³/h	442 m³/h	1767 m³/h	2121 m³/h
300	12"	7,6 m³/h	636 m³/h	2545 m³/h	3054 m³/h
350	14"	10,4 m³/h	866 m³/h	3464 m³/h	4156 m³/h
400	16"	14 m³/h	1131 m³/h	4524 m³/h	5429 m³/h
450	18"	17 m³/h	1431 m³/h	5725 m³/h	6870 m³/h
500	20"	21 m³/h	1767 m³/h	7068 m³/h	8482 m³/h
550	22"	26 m³/h	2138 m³/h	8553 m³/h	10263 m³/h
600	24"	31 m³/h	2545 m³/h	10178 m³/h	12214 m³/h
700	28"	42 m³/h	3464 m³/h	13854 m³/h	16625 m³/h
750	30"	48 m³/h	3976 m³/h	15904 m³/h	19085 m³/h
800	32"	54 m³/h	4523 m³/h	18096 m³/h	21714 m³/h
900	36"	69 m³/h	5725 m³/h	22902 m³/h	27482 m³/h
1000	40"	85 m³/h	7068 m³/h	28274 m³/h	33929 m³/h
1200	48"	122 m³/h	10178 m³/h	40714 m³/h	48857 m³/h
1400	56"	166 m³/h	13854 m³/h	55416 m³/h	66499 m³/h

Larger diameters upon request

Product line overview

Electromagnetic flow meters
Ultrasonic flow meters
Weirs and flumes
Turbine meters
Oscillating piston meters
Rotating disc meters
Impeller meters
Vortex meters
Variable area flow meters
Differential pressure flow meters
Venturi tubes
Mass meters
Heat meters
Hydraulic testers
Flow calibrators
Lubrication meters
Oil management systems
Control valves
Concrete finishing products



Badger Meter Europa

Badger Meter Europa GmbH

Nürtinger Str. 76
72639 Neuffen
Germany
Tel. +49-70 25-92 08-0
Fax +49-70 25-92 08-15
badger@badgermeter.de
www.badgermeter.de

For Switzerland
Badger Meter Swiss AG
Mittelholzerstr. 8
3006 Bern
Switzerland
Tel. +41 31 932 01 11
Fax +41 31 931 08 67
info@badgermeter.ch
www.badgermeter.ch

For the USA and Canada
Badger Meter, Inc.
P.O. Box 245036
Milwaukee, WI 53224-9536
USA
Tel. +1-414-355-04 00
Fax +1-414-355-74 99
infocentral@badgermeter.com
www.badgermeter.com

For Asia
Badger Meter Europa GmbH
Singapore Branch
80 Marine Parade Road
#21-06 Parkway Parade
Singapore 449269
Singapore
Tel. +65-63 46 48 36
Fax +65-63 46 48 37
awang@badgermeter.com

For Slovakia
Badger Meter Slovakia s. r. o.
Racianska 109/B
83102 Bratislava
Slovakia
Tel. +421-2-44 63 83 01
Fax +421-2-44 63 83 03
badgermeter@badgermeter.sk
www.badgermeter.sk

For the United Arab Emirates
Badger Meter Europe
Middle East Branch Office
Dubai Silicon Oasis
Head Quarter Building
Wing C, Office #C209
Dubai / UAE
Tel. +971-4-371 2503
Fax +971-4-371 2504
gramaswamy@badgermeter.com

For Mexico
Badger Meter de las
Americas S. A. de C. V.
Pedro Luis Ogazon #32
Col. Guadalupe Inn
Mexico, D. F. 01020
Mexico
Tel. +52-55-56 62-08 82
Fax +52-55-56 62-75 81
bmdla@badgermeter.com

For China
Badger Meter, Inc.
Shanghai Representative
Office 7-1202
99 Hangzhong Road
Minhang District
Shanghai 201101
China
Tel. +86-21-57 63-54 12
Fax +86-21-57 63-54 12
rjiang@badgermeter.com

For the Czech Republic
Badger Meter Czech
Republic s. r. o.
Marikova 2082/26
62100 Brno
Czech Republic
Tel. +420-5-41 42 04 11
Fax +420-5-41 22 97 24
obchod@badgermeter.cz
www.badgermeter.cz

MID__UB__99__01__1606



Jeder Tropfen zählt.